



PRODUCT BULLETIN

FROM: Marketing Department

PRODUCT NAME:	City Plank
CONSTRUCTION:	Multi-Ply Cross Directional Construction For Maximum Dimensional Stability
INSTALLATION:	Install On Grade, Above Grade, or Below Grade
INSTALLATION METHOD:	Glue Down, Staple Down, Floating
SUBFLOORS:	Concrete, 5/8" or 3/4" Plywood, 3/4" OSB (Oriented Strand Board),
WOOD SPECIES:	Brazilian Cherry, Santos Mahogany, Australian Cypress, Brazilian Walnut Teak
COLORS:	All Above Species finished with Natural transparent finish
SPECIFICATIONS:	THICKNESS: 1/2" WIDTHS: 3 9/16" & 4 3/4" LENGTHS: 1/2(17"-47") / 4 3/4(17"-84"
EDGE TREATMENT:	SIDES: Micro-bevel ENDS: Micro-bevel
FINISH:	Enhanced Aluminum Oxide Urethane Finish
FINISH APPEARANCE:	Semi-gloss
WARRANTY	Finish - 1 Year Light Commercial & 25 Year Residential Finish
REFINISHING :	Can be "screened and recoated" due to excessive wear or "sanded and refinished" due to damage to a large area if required by a professional refinisher.

PRODUCTS:	SPECIES	COLOR	Size (width)	PRODUCT CODE
	Brazilian Cherry	Natural	3 9/16" (90mm)	FORCP3BCHRY35
	Brazilian Cherry	Natural	4 3/4" (120mm)	FOCP4BCHRY475
	Santos Mahogany	Natural	3 9/16" (90mm)	FORCP3SMAH35
	Santos Mahogany	Natural	4 3/4" (120mm)	FORCP4SMAH475
	Australian Cypress	Natural	4 3/4" (120mm)	FORCP4ACYP475
	Brazilian Walnut	Natural	3 9/16" (90mm)	FORCP3BWAL35
	Brazilian Walnut	Natural	4 3/4" (120mm)	FORCP4BWAL475
	Teak	Natural	3 9/16" (90mm)	FORCP3TEAK35
	Square Feet Per Carton:		3 9/16" - 30.5 SF/CTN	4 3/4" - 26.35 SF/CTN
	Shipping Weight Per Carton:		55 - 62 lbs/CTN	50 - 55 lbs/CTN

PRODUCT FEATURES:	<ol style="list-style-type: none"> 1. City Plank's engineered construction allows the product to be installed over dried concrete subfloors and above, on or below grade installations. 2. The semi-gloss transparent finish highlights the deep beauty of the exotic wood species. 3. City Plank's thick "Sawn-Cut" or "Sliced-Cut" hardwood wear surface provides a true "Solid" appearance unlike "Rotary-Cut" veneer flooring. 4. Due to the 3mm wear surface, City Plank carries a 3-sanding warranty for future value. 5. Forest Accents manufactures all complementing City Plank moldings and transitions to coordinate with our City Plank floors. 6. Multi-Ply construction assures maximum dimensional stability. This construction is less susceptible to expansion and contraction and is perfect for rooms with varying degrees of humidity. 7. Installer friendly due to a wide range of installation options. City Plank wood flooring can be glued, stapled, or nailed. 8. Due to the enhanced Aluminum Oxide Finish, our products perform well under light/medium commercial traffic with the proper maintenance plan.
--------------------------	--



PRODUCT BULLETIN

FROM: Marketing Department

PRODUCT NAME:	Listone Milano Collection - "Maxi"
CONSTRUCTION:	Multi-Ply Cross Directional Construction For Maximum Dimensional Stability
INSTALLATION:	Install On Grade, Above Grade, or Below Grade
INSTALLATION METHOD:	Glue Down, Staple Down
SUBFLOORS:	Concrete, 5/8" or 3/4" Plywood, 3/4" OSB (Oriented Strand Board),
WOOD SPECIES:	Afrosomia, American Maple, Santos Mahogany, Doussie, Sapele, Wenge
COLORS:	All Above Species finished with Natural transparent finish
SPECIFICATIONS:	THICKNESS: 1/2" WIDTHS: 3 9/16" LENGTHS: 17" - 47"
EDGE TREATMENT:	SIDES: Square Edges ENDS: Square Ends
FINISH:	Enhanced Aluminum Oxide Urethane Finish
FINISH APPEARANCE:	Matte (20° +/- 5)
WARRANTY	Finish - 1 Year Light Commercial & 25 Year Residential Finish
REFINISHING :	Can be "screened and recoated" due to excessive wear or "sanded and refinished" due to damage to a large area if required by a professional refinisher.

PRODUCTS:	SPECIES	COLOR	Size (width)	PRODUCT CODE
	African Afrosomia	Natural	3 9/16" (90mm)	FOR MAXI AFROMOSIA
	American Maple	Natural	3 9/16" (90mm)	FOR MAXI MAPLE
	Santos Mahogany	Natural	3 9/16" (90mm)	FOR MAXI SANMAHOG
	African Doussie	Natural	3 9/16" (90mm)	FOR MAXI DOUSSIE
	African Sapele	Natural	3 9/16" (90mm)	FOR MAXI SAPELE
	African Wenge	Natural	3 9/16" (90mm)	FOR MAXI WENGE
Square Feet Per Carton:			3 9/16" - 24.43 SF/CTN	
Shipping Weight Per Carton:			46.3 lbs/CTN	

PRODUCT FEATURES:	<ol style="list-style-type: none"> Listone Milano Maxi's engineered construction allows the product to be installed over dried concrete subfloors and above, on or below grade installations. The low gloss matte transparent finish highlights the deep beauty of the exotic wood species. Listone Milano Maxi's thick "Sawn-Cut" hardwood wear surface provides a true "Solid" appearance unlike "Rotary-Cut" veneer flooring. Due to the 4mm wear surface, Listone Milano carries a 3-sanding warranty for future value. Forest Accents manufactures all complementing Listone Milano moldings and transitions to coordinate with the wood flooring. Multi-Ply construction assures maximum dimensional stability. This construction is less susceptible to expansion and contraction and is perfect for rooms with varying degrees of humidity. Installer friendly due to a wide range of installation options. Listone Milano Maxi wood flooring can be glued, stapled, or nailed. Due to the enhanced Aluminum Oxide Finish, our products perform well under light/medium commercial traffic with the proper maintenance plan.
--------------------------	--

Forest Accents 2655 Dawin Road N. Jacksonville, FL 32207



FROM: Marketing Department

PRODUCT NAME: Isles of the Mediterranean Collection (Mikonos Plank & Capri Plank)

CONSTRUCTION: Multi-Ply Cross Directional Construction For Maximum Dimensional Stability

INSTALLATION: Install On Grade, Above Grade, or Below Grade

INSTALLATION METHOD: Glue Down, Staple Down

SUBFLOORS: Concrete, 5/8" or 3/4" Plywood, 3/4" OSB (Oriented Strand Board),

WOOD SPECIES: Brazilian Cherry, African Santos, African Teak, Brazilian Walnut, Tigerwood,

COLORS: Santos Mahogany, African Mahogany, Cumaru, Amendoim & Oak

SPECIFICATIONS:

MIKONOS	THICKNESS: 5/16"	WIDTHS: 4"	LENGTHS: 12" - 48"
CAPRI	THICKNESS: 1/2"	WIDTHS: 5"	LENGTHS: 12" - 84"

EDGE TREATMENT: SIDES: Micro-bev ENDS: Micro-bev

FINISH: Enhanced Aluminum Oxide Urethane Finish

FINISH APPEARANCE: Semi Gloss

WARRANTY: Mikonos has a 15 Year Residential Finish / Capri has a 25 Year Residential Finish

REFINISHING: Can be "screened and recoated" due to excessive wear or "sanded and refinished" due to damage to a large area if required by a professional refinisher.

PRODUCTS:

	SPECIES	COLOR	Size (width)	PRODUCT CODE
Mikonos Plank	Red Oak	Natural	5/16" x 4"	FOR MIKO RONATURAL
	Oak	Gunstock	5/16" x 4"	FOR MIKO GUNSTOCK
	Brazilian Cherry	Natural	5/16" x 4"	FOR MIKO BRCHERRY
	African Mahogany	Natural	5/16" x 4"	FOR MIKO AFMAHOGNY
	Cumaru	Natural	5/16" x 4"	FOR MIKO CUMARU
	Tigerwood	Natural	5/16" x 4"	FOR MIKO TIGERWOOD
Capri Plank	Brazilian Cherry	Natural	1/2" x 5"	FOR CAPR BRCHERRY
	African Santos	Stained	1/2" x 5"	FOR CAPR AFSANTOS
	African Teak	Natural	1/2" x 5"	FOR CAPR AFTEAK
	Brazilian Walnut	Natural	1/2" x 5"	FOR CAPR BRWALNUT
	Tigerwood	Natural	1/2" x 5"	FOR CAPR TIGERWOOD
	Santos Mahogany	Natural	1/2" x 5"	FOR CAPR SAMAHOGNY
Amendoim	Natural	1/2" x 5"	FOR CAPR AMENDOIM	
Square Feet Per Carton:			Mikonos - 32.15 SF/CTN / Capri - 46.59 SF/CTN	
Shipping Weight Per Carton:			Mikonos - 36 lbs/CTN / Capri - 84 lbs/CTN	

PRODUCT FEATURES:

1. Capri Plank & Mikonos Plank engineered construction allows the product to be installed over dried concrete subfloors and above, on or below grade installations.
2. The transparent finish highlights the deep beauty of the exotic wood species.
3. Capri Plank & Mikonos Plank hardwood wear surface provides a true "Solid" appearance unlike "Rotary-Cut" veneer flooring.
4. Forest Accents manufactures all complementing moldings and transitions to coordinate with the wood flooring.
5. Multi-Ply construction assures maximum dimensional stability. This construction is less susceptible to expansion and contraction and is perfect for rooms with varying degrees of humidity.
6. Installer friendly due to a wide range of installation options.
7. Due to the enhanced Aluminum Oxide Finish, our products perform well under light/medium commercial traffic with the proper maintenance plan.



PRODUCT BULLETIN

FROM: Marketing Department

PRODUCT NAME:	Colonial Classics by City Plank
CONSTRUCTION:	Multi-Ply Cross Directional Construction For Maximum Dimensional Stability
INSTALLATION:	Install On Grade, Above Grade, or Below Grade
INSTALLATION METHOD:	Glue Down, Staple Down, Floating
SUBFLOORS:	Concrete, 5/8" or 3/4" Plywood, 3/4" OSB (Oriented Strand Board),
WOOD SPECIES:	American Hickory, American Walnut
(COLORS)	

SPECIFICATIONS:	THICKNESS: 1/2"	WIDTHS: 4 3/4"	LENGTHS: Random Lengths 17" - 84"
EDGE TREATMENT:	SIDES: Micro-bevel	ENDS: Micro-bevel	
FINISH:	Enhanced Aluminum Oxide Urethane Finish		
FINISH APPEARANCE:	Wire Brushed with Matte Finish		
WARRANTY	Finish - 1 Year Light Commercial & 25 Year Residential Finish		
REFINISHING :	Can be "screened and recoated" due to excessive wear or "sanded and refinished" due to damage to a large area if required by a professional refinisher.		

PRODUCTS:	SPECIES	COLOR	Size (width)	PRODUCT CODE
	Hickory	Statehouse	4 3/4" (120mm)	FOR COL STATEHOUS
	Hickory	Savannah	4 3/4" (120mm)	FOR COL SAVANNAH
	American Walnut	Providence	4 3/4" (120mm)	FOR COL PROVIDENC
	American Walnut	Williamsburg	4 3/4" (120mm)	FOR COL WILLIAMS
	Square Feet Per Carton:			4 3/4" - 26.35 SF/CTN
	Shipping Weight Per Carton:			50 - 55 lbs/CTN

PRODUCT FEATURES:	<ol style="list-style-type: none"> 1. Colonial Classics engineered construction allows the product to be installed over dried concrete subfloors and above, on or below grade installations. 2. The Wire Brushed textured surface brings out the wood specie graining. 3. Colonial Classics thick "Sawn-Cut" or "Sliced-Cut" hardwood wear surface provides a true "Solid" appearance unlike "Rotary-Cut" veneer flooring. 4. Due to the 3mm wear surface, Colonial Classics carries a 3-sanding warranty for future value. 5. Forest Accents manufactures all complementing Colonial Classics moldings and transitions to coordinate with our Colonial Classics floors. 6. Multi-Ply construction assures maximum dimensional stability. This construction is less susceptible to expansion and contraction and is perfect for rooms with varying degrees of humidity. 7. Installer friendly due to a wide range of installation options. Colonial Classics wood flooring can be glued, stapled, or nailed. 8. Due to the enhanced Aluminum Oxide Finish, our products perform well under light/medium commercial traffic with the proper maintenance plan.
--------------------------	--

Forest Accents 2655 Dawin Road N. Jacksonville, FL 32207



PRODUCT BULLETIN

FROM: Marketing Department

PRODUCT NAME:	Victoria Plank			
CONSTRUCTION:	Multi-Ply Cross Directional Construction For Maximum Dimensional Stability			
INSTALLATION:	Install On Grade, Above Grade, or Below Grade			
INSTALLATION METHOD:	Glue Down, Staple Down			
SUBFLOORS:	Concrete, 5/8" or 3/4" Plywood, 3/4" OSB (Oriented Strand Board),			
WOOD SPECIES:	African Mahogany, African Teak, African Rosewood, African Oak, African Wenge			
(colors)				
SPECIFICATIONS:	THICKNESS: 1/2"	WIDTHS:	Nom. 5" (4.92")	LENGTHS: Random Lengths 12" to 48"
EDGE TREATMENT:	SIDES: Micro-bevel		ENDS: Micro-bevel	
FINISH:	Enhanced Ceramic Anti-scratch Urethane Finish			
FINISH APPEARANCE:	Matte Finish			
WARRANTY	Finish - 1 Year Light Commercial & 15 Year Residential Finish			
REFINISHING :	Can be "screened and recoated" due to excessive wear.			
PRODUCTS:	SPECIES	COLOR	Size (width)	PRODUCT CODE
	African Mahogany	Natural	Nominal 5" (125mm)	FORVICAFAH5
	African Teak	Natural	Nominal 5" (125mm)	FORVICAFTK5
	African Oak	Natural	Nominal 5" (125mm)	FORVICAFOAK5
	African Wenge	Natural	Nominal 5" (125mm)	FORVICAFWENGE5
	Square Feet Per Carton:		9.92 SF/CTN	
	Shipping Weight Per Carton:		16 lbs/CTN	

- PRODUCT FEATURES:**
- Victoria Plank's engineered construction allows the product to be installed over dried concrete subfloors and above, on or below grade installations.
 - Matte finish highlights the deep beauty of the African Species and reduces the reflection of scuff and scratch marks in high traffic areas.
 - Victoria Plank's "Sawn-Cut" or "Sliced-Cut" hardwood wear surface provides a true "Solid" appearance unlike "Rotary-Cut" veneer flooring.
 - Wide Plank appeal with striking bold & radiant color make Victoria Plank a popular choice
 - Forest Accents manufactures all complementing Victoria Plank moldings and transitions to coordinate with our Victoria Plank floors.
 - Multi-Ply construction assures maximum dimensional stability. This construction is less susceptible to expansion and contraction and is perfect for rooms with varying degrees of humidity.
 - Installer friendly due to a wide range of installation options. Victoria Plank wood flooring can be glued or stapled.
 - Due to the enhanced Ceramic "Anti-scratch" Finish, our products perform well under light/medium commercial traffic with the proper maintenance plan.



PRODUCT BULLETIN

FROM: Marketing Department

PRODUCT NAME:	Destin Plank V (5")			
CONSTRUCTION:	Multi-Ply Cross Directional Construction For Maximum Dimensional Stability			
INSTALLATION:	Install On Grade, Above Grade, or Below Grade			
INSTALLATION METHOD:	Glue Down, Staple Down			
SUBFLOORS:	Concrete, 5/8" or 3/4" Plywood, 3/4" OSB (Oriented Strand Board),			
WOOD SPECIES:	Red Oak & White Oak			
(colors)				
SPECIFICATIONS:	THICKNESS: 3/8"	WIDTHS: 5"	LENGTHS:	Random Lengths 12" to 48"
EDGE TREATMENT:	SIDES: Micro-bevel		ENDS: Micro-bevel	
FINISH:	Enhanced Aluminum Oxide Urethane Finish			
FINISH APPEARANCE:	Open grained surface with a matte low-gloss finish			
WARRANTY	Finish - 1 Year Light Commercial & 15 Year Residential Finish			
REFINISHING :	Can be "screened and recoated" due to excessive wear.			

PRODUCTS:	SPECIES	COLOR	Size (width)	PRODUCT CODE
	Red Oak	Natural	5" (127mm)	FOR DES5 OAKNATURL
	White Oak	Buckskin	5" (127mm)	FOR DES5 BUCKSIN
	White Oak	Autumn	5" (127mm)	FOR DES5 OAKAUTUMN
	White Oak	Honey	5" (127mm)	FOR DES5 OAKHONEY
	White Oak	Dark Chocolate	5" (127mm)	FOR DES5 DARKCHOC
	Square Feet Per Carton:		36.38 SF/CTN	
	Shipping Weight Per Carton:		58 lbs/CTN	

PRODUCT FEATURES:	<ol style="list-style-type: none"> Destin Plank's engineered construction allows the product to be installed over dried concrete subfloors and above, on or below grade installations. The open grained low gloss surface conceals wearing. When price and quality are the objective, nothing compares to Destin Plank V. Forest Accents manufactures all complementing Destin Plank moldings and transitions to coordinate with our Destin Plank floors. Multi-Ply construction assures maximum dimensional stability. This construction is less susceptible to expansion and contraction and is perfect for rooms with varying degrees of humidity. Installer friendly due to a wide range of installation options. Destin Plank wood flooring can be glued or stapled. Due to the aluminum oxide finish, our products perform well under light/medium commercial traffic with the proper maintenance plan.
--------------------------	--

Forest Accents 2655 Dawin Road N. Jacksonville, FL 32207



PRODUCT BULLETIN

FROM: Marketing Department

PRODUCT NAME:	Timeless Textures
CONSTRUCTION:	Multi-Ply Cross Directional Construction For Maximum Dimensional Stability
INSTALLATION:	Install On Grade, Above Grade, or Below Grade
INSTALLATION METHOD:	Glue Down, Staple Down, Nail Down
SUBFLOORS:	Concrete, 5/8" or 3/4" Plywood, 3/4" OSB (Oriented Strand Board),
WOOD SPECIES:	Maple, American Hickory, American Walnut, Birch
(COLORS)	

SPECIFICATIONS:	THICKNESS: 9/16"	WIDTHS: 5"	LENGTHS: Random Lengths 12"- 47"
EDGE TREATMENT:	SIDES: Micro-bevel	ENDS: Micro-bevel	
FINISH:	Handscraped and Distressed prefinished flooring		
FINISH APPEARANCE:	Matte		
WARRANTY	Finish - 1 Year Light Commercial & 25 Year Residential Finish		
REFINISHING :	Can be "screened and recoated" due to excessive wear or "sanded and refinished" due to damage to a large area if required by a professional refinisher.		

PRODUCTS:	SPECIES	COLOR	Size (width)	PRODUCT CODE
	Original Series			
	Maple	Bronze	5"	FOR TEX BRONZE
	Maple	Cappuccino	5"	FOR TEX CAPCHINO
	Maple	Harvest	5"	FOR TEX HARVEST
	Maple	Wheat	5"	FOR TEX WHEAT
	Maple	Tawny	5"	FOR TEX TAWNY
	American Walnut	Antique	5"	FOR TEX ANTWALNUT
	American Walnut	Black Mink	5"	FOR TEX BLKMINK
	Birch	Burgundy	5"	FOR TEX BURGUNDY
	Birch	Butterscotch	5"	FOR TEX BUTSCOTCH
	Birch	Kahlua	5"	FOR TEX KAHLUA
	Hickory	Butternut	5"	FOR TEX BUTTERNUT
	Hickory	Hazelnut	5"	FOR TEX HAZELNUT
	Square Feet Per Carton:			23 SF/CTN
	Shipping Weight Per Carton:			50 lbs/CTN

PRODUCT FEATURES:	<ol style="list-style-type: none"> 1. Timeless Textures engineered construction allows the product to be installed over dried concrete subfloors and above, on or below grade installations. 2. The distressed textured surface highlights the wood color, character & graining 3. Timeless Textures offers 12 of the most exquisite colors on 4 prized wood species. 4. Due to the 2mm wear surface, Timeless Textures provides long term value. 5. Forest Accents manufactures all complementing Timeless Textures moldings and transitions to coordinate with our floors. 6. Multi-Ply construction assures maximum dimensional stability. This construction is less susceptible to expansion and contraction and is perfect for rooms with varying degrees of humidity. 7. Installer friendly due to a wide range of installation options. Timeless Textures wood flooring can be glued, stapled, or nailed. 8. Due to the enhanced Aluminum Oxide Finish, our products perform well under light/medium commercial traffic with the proper maintenance plan.
--------------------------	--



PRODUCT BULLETIN

FROM: Marketing Department

PRODUCT NAME:	Crafted Textures
CONSTRUCTION:	Multi-Ply Cross Directional Construction For Maximum Dimensional Stability
INSTALLATION:	Install On Grade, Above Grade, or Below Grade
INSTALLATION METHOD:	Glue Down, Staple Down, Nail Down
SUBFLOORS:	Concrete, 5/8" or 3/4" Plywood, 3/4" OSB (Oriented Strand Board),
WOOD SPECIES:	Birch, Maple, Hickory & Reclaimed Elm
(COLORS)	
SPECIFICATIONS:	THICKNESS: 1/2" WIDTHS: 3.5", 5", 6" LENGTHS: Random Lengths 12"- 47"
EDGE TREATMENT:	SIDES: Micro-bevel ENDS: Micro-bevel
FINISH:	Handscraped and Distressed prefinished flooring
FINISH APPEARANCE:	Matte
WARRANTY	Finish - 1 Year Light Commercial & 25 Year Residential Finish
REFINISHING :	Can be "screened and recoated" due to excessive wear or "sanded and refinished" due to damage to a large area if required by a professional refinisher.

PRODUCTS:	SPECIES	COLOR	Size (width)	PRODUCT CODE
	Birch	Sunset	5"	FOR CRF SUNSET2
	Birch	Sierra Brown	5"	FOR CRF SIERRA2
	Birch	Sable	5"	FOR CRF SABLE2
	Birch	French Roast	5"	FOR CRF ROAST2
	Maple	Smoke	5"	FOR CRF SMOKE
	Hickory	Natural	5"	FOR CRF HICKNATRL
	Hickory	Dusk	5"	FOR CRF DUSK
	Hickory	Rawhide	5"	FOR CRF RAWHIDE
	Hickory	Sienna	5"	FOR CRF SIENNA
	Reclaimed Elm	St. Augustine	3.5", 5", 6"	FOR CRF AUGSTINE
	Reclaimed Elm	Savannah	3.5", 5", 6"	FOR CRF SAVANNAH
	Reclaimed Elm	Charleston	3.5", 5", 6"	FOR CRF CHARLESTN
	Square Feet Per Carton:			26.24 SF/CTN
	Shipping Weight Per Carton:			46 lbs/CTN

PRODUCT FEATURES:	<ol style="list-style-type: none"> 1. Crafted Textures engineered construction allows the product to be installed over dried concrete subfloors and above, on or below grade installations. 2. The distressed textured surface highlights the wood color, character & graining 3. Crafted Textures offers 12 of the most exquisite colors on birch, maple, hickory & elm. 4. Due to the 2mm wear surface, Crafted Textures provides long term value. 5. Forest Accents manufactures all complementing Crafted Textures moldings and transitions to coordinate with our floors. 6. Multi-Ply construction assures maximum dimensional stability. This construction is less susceptible to expansion and contraction and is perfect for rooms with varying degrees of humidity. 7. Installer friendly due to a wide range of installation options. Crafted Textures wood flooring can be glued, stapled, or nailed. 8. Due to the enhanced Aluminum Oxide Finish, our products perform well under light/medium commercial traffic with the proper maintenance plan.
--------------------------	---



PRODUCT BULLETIN

FROM: Marketing Department

PRODUCT NAME:	Solid Bamboo Flooring
CONSTRUCTION:	Solid Bamboo milled with Tongue and Grooves on all four sides
INSTALLATION:	Install On Grade or Above Grade
INSTALLATION METHOD:	Glue Down, Nail Down
SUBFLOORS:	5/8" or 3/4" Plywood, 3/4" OSB (Oriented Strand Board),
WOOD SPECIES:	Bamboo
COLORS:	Horizontal Natural, Horizontal Carbonized, Vertical Natural, Vertical Carbonized Strand Woven Natural & Strand Woven Carbonized
SPECIFICATIONS:	THICKNESS: 5/8" WIDTHS: 3 3/4" LENGTHS: 37 3/8"
EDGE TREATMENT:	SIDES: Micro-bevel ENDS: Micro-bevel
FINISH:	Enhanced Aluminum Oxide Urethane Finish
FINISH APPEARANCE:	Matte Finish
WARRANTY:	Finish - 1 Year Light Commercial & 25 Year Residential Finish
REFINISHING :	Can be "screened and recoated" due to excessive wear or "sanded and refinished" due to damage to a large area if required by a professional refinisher.

PRODUCTS:	SPECIES	COLOR	CUT STYLE	PRODUCT CODE
	Bamboo	Natural	Horizontal	TME BAM SOLNATHOR
Bamboo	Natural	Vertical	TME BAM SOLNATVER	
Bamboo	Natural	Strand Woven	TME BAM STRANNATL	
Bamboo	Carbonized	Horizontal	TME BAM SOLCARHOR	
Bamboo	Carbonized	Vertical	TME BAM SOLCARVER	
Bamboo	Carbonized	Strand Woven	TME BAM STRANCARB	
Square Feet Per Carton:			23.8 for Vertical/Horizontal / 17.11 for strand Woven	
Shipping Weight Per Carton:			49 lbs for Vert/Horiz / 57 lbs for Strand Woven	

- PRODUCT FEATURES:**
- Bamboo flooring is harder than domestic Red Oak and more stable than domestic Maple.
 - Matte finish highlights the deep beauty of the bamboo and reduces the reflection of scuff and scratch marks in high traffic areas.
 - Bamboo Flooring is considered a green environmentally friendly product. Bamboo is fast growing and said to grow 1" per day (30 feet per year). It is ready for harvesting in 4-6 years.
 - Bamboo Flooring is one of the most popular design trends over the last 10 years.
 - Forest Accents manufactures all complementing Bamboo moldings and transitions to coordinate with our Bamboo Floors.
 - Forest Accents Solid Flooring is strictly dried to a moisture content between 8% - 10%. This reduced the chances of extreme cupping, crowning, warping, twisting or shrinkage.
 - Installer friendly due to a wide range of installation options. Solid Bamboo Flooring can be glued or nailed.
 - Due to the enhanced Aluminum Oxide Finish, our products perform well under light/medium commercial traffic with the proper maintenance plan.



PRODUCT BULLETIN

FROM: Marketing Department

DATE: January 1, 2008

PRODUCT NAME:	ProPlank & ProStrip		
CONSTRUCTION:	Multi-Ply Cross Directional Construction For Maximum Dimensional Stability		
INSTALLATION:	Install On Grade, Above Grade, or Below Grade		
INSTALLATION METHOD:	Glue Down, Staple Down		
SUBFLOORS:	Concrete, 5/8" or 3/4" Plywood, 3/4" OSB (Oriented Strand Board),		
WOOD SPECIES:	Brazilian Cherry, Santos Mahogany, Australian Cypress, Brazilian Walnut, Red Oak		
COLORS:	All Above Species are unfinished		
SPECIFICATIONS:	THICKNESS: 1/2"	WIDTHS: 2 1/4"; 3 9/16"; 4 3/4"	LENGTHS: Random Lengths
EDGE TREATMENT:	SIDES: Square Edges	ENDS: Square Edges	
FINISH:	None; Product is pre-sanded and unfinished		
FINISH APPEARANCE:	None		
WARRANTY	3-Sanding Warranty & Lifetime Structural Warranty		
REFINISHING :	Can be "screened and recoated" due to excessive wear or "sanded and refinished" due to damage to a large area if required by a professional refinisher.		

PRODUCTS:	SPECIES	COLOR	Size (width)	PRODUCT CODE
	Brazilian Cherry	Unfinished	4 3/4" (120mm)	FORPP4BCHRYUF47
Santos Mahogany	Unfinished	4 3/4" (120mm)	FORPP4SMAHUF475	
Australian Cypress	Unfinished	4 3/4" (120mm)	FORPP4ACYPUF475	
Brazilian Walnut	Unfinished	4 3/4" (120mm)	FORPP4BWALUF475	
Red Oak	Unfinished	2 1/4" (57mm)	FORPRSROAKUF225	
Red Oak	Unfinished	3 9/16" (90mm)	FORPP3ROAKUF35	
Red Oak	Unfinished	4 3/4" (120mm)	FORPRSROAKUF475	
Square Feet Per Carton:		3 9/16" - 30.5 SF/CTN	4 3/4" - 26.35 SF/CTN	
Shipping Weight Per Carton:		55 - 62 lbs/CTN	50 - 55 lbs/CTN	

- PRODUCT FEATURES:**
1. ProPlank's engineered construction allows the product to be installed over dried concrete subfloors and above, on or below grade installations.
 2. ProPlank's engineered construction reduces delays in acclimation time needed for solids.
 3. ProPlank's thick "Sawn-Cut" or "Sliced-Cut" hardwood wear surface provides a true "Solid" appearance unlike "Rotary-Cut" veneer flooring.
 4. Due to the 3mm wear surface, ProPlank carries a 3-sanding warranty for future value.
 5. Forest Accents manufactures all complementing ProPlank moldings and transitions to coordinate with our ProPlank floors.
 6. Multi-Ply construction assures maximum dimensional stability. This construction is less susceptible to expansion and contraction and is perfect for rooms with varying degrees of humidity.
 7. Installer friendly due to a wide range of installation options. ProPlank wood flooring can be glued, stapled, or nailed.
 8. ProPlank is factory pre-sanded unlike solid wood floors. This eliminates the need for 2 machine sandings. The net effect is a great time savings over solid unfinished floors